

## **OSMO® Liquid Wax Cleaner**



**OSMO Hardwax Oil** finish is extremely durable, but like any finish, it will show wear over time, especially in high-traffic areas such as kitchen, main entries and stairways. Timely use of OSMO Liquid Wax Cleaner restores the finish and helps to keep it lasting indefinitely. This product can also be used on any waxed woodwork.

Liquid Wax Cleaner contains carnauba and candillila wax, the same two natural waxes used in Hardwax Oil. These are both plant-based waxes that regrow rapidly. Liquid Wax Cleaner also contains medical-quality paraffins and odor-free mineral spirits, both of which are petroleum products. The cleaner does not include biocides or preservatives.

First clean the floor or wood thoroughly, preferably with a moist cloth or mop dampened in OSMO Wash and Care diluted in water. Wring out the cloth or mop thoroughly so that no water puddles. Allow to dry. Then moisten fine steel wool or a white Scotchbrite pad with a small amount of OSMO Liquid Wax Cleaner. Rub this onto the surface. Allow to dry for 30 to 60 minutes, until the material dries to a haze. Buff lightly with a soft cotton cloth.

If damage has been done to a specific area of the floor, or if high-traffic areas are not maintained as above, it is possible to recoat the floor with OSMO Hardwax Oil. Clean and sand the area, then apply the finish by hand. Use a white Scotchbrite pad dipped into the finish and scrub it in with a vigorous circular stroke. Wipe up immediately so that no material is left on the floor.

Be aware that Liquid Wax Cleaner or even a fresh coat of Hardwax Oil will restore the finish, but neither product will fill in damaged wood.

## One liter is enough to refresh 1,000 square feet.

SIGNATURE HARDWOODS™ 866.554.4252 signaturehardwoods.com sales@signaturehardwoods.com