



# PALLMANN® P13

Tongue & Groove Adhesive

## Description

Quick-drying dispersion wood adhesive for gluing the tongue and groove on prefinished wood and laminate flooring. Also suitable for use as a universal wood adhesive on many wood species and wood-based materials. Excellent for gluing wood plugs and dowels. For indoor use only. Solvent-free.



UNIVERSAL  
WOOD  
ADHESIVE

## Application

Cut off nozzle tip to fit desired joint size. Apply P13 to the surface of the tongue or into the groove. Join wood parts together during dry time, applying force if necessary with a wooden tapping block and/or straps. Remove all traces of extruded glue immediately with a damp cloth or PALLMANN® Clean Box.

## Technical Data

Application temperature:	Above 60 °F (surface temp.)
Drying time:	5 – 10 minutes*
Load bearing:	After approx. 12 hours*
Final adhesive strength:	After 1 – 2 days*
Coverage:	80 – 500 lineal feet per bottle depending on joint size

\*At 68°F and 65% relative humidity.

## Disposal

Dispose of empty containers according to local, state and federal regulations.

**Uzin Utz**  
NORTH AMERICA

PALLMANN | A Brand of Uzin Utz Group  
Aurora, CO 80011 USA | Phone: 720.374.4810  
pallmann.us@uzin-utz.com | pallmann.us



**PALLMANN®**

wood floors. protected

Rev 02/19/18