



# Superb Sound Underlayment

Suitable for use under ceramic tile,  
stone and hardwood floors



**Superb Sound  
Insulation**



**Crack  
Suppressant**



**Heat-Safe  
Underlayment**



**Environmentally  
Friendly**

Available in 3 mm and 6 mm thickness





FlexiKork® is a flat, resilient underlayment that is used directly under a variety of floor finishes, yielding exceptional results especially under hard surface flooring and over concrete and wood joist construction.

FEATURES	BENEFITS
<b>Made from 100% resilient recycled rubber and cork</b>	Environmentally friendly, green product that meets LEED criteria. FlexiKork® can potentially qualify for up to 9 points toward a project's LEED certification. Passed all indoor air quality tests for low VOC emissions.
<b>Anti-Microbial</b>	Prevents/inhibits the growth of microorganisms.
<b>Truly universal underlayment</b>	Compatible under most types of grouted and non-grouted flooring installations including ceramic tile, stone, solid & engineered hardwood, laminate, vinyl and carpet.
<b>Can thin-set tile and stone directly to the product</b>	No special tile/stone adhesive is needed. Can thin-set tile and stone directly to the product per ASTM C627. Saves time, labor and money!
<b>Shock &amp; stress relieving</b>	Shock absorbing, flexible material with stress relieving capabilities, will not break down or move under load - strong enough for trades to work on. Prevents tile from cracking.
<b>Superb sound control</b>	Outperforms cork, felt, polyethylene, fiberglass and nylon matrix. Provides the highest IIC and STC rating backed by many independent laboratory and field tests.
<b>Suitable for application in variety of housing</b>	Extremely broad spectrum of uses in virtually every housing including: multifamily housing, high rises, single-family homes and commercial buildings.
<b>Inhibits sound transfer through floor-ceiling assembly</b>	Absorbs sound and vibration. Keeps noises from traveling through floor-ceiling assembly.
<b>Increases IIC and STC ratings</b>	Meets and exceeds tough building code requirements while adding less than 1/2" of floor height.
<b>Suitable for all floor heating systems</b>	Can be installed over radiant heating systems with no adverse effects.
<b>Low construction height</b>	Reduces gaps in floor when moving from one hard surface to another. Saves space, reduces the use of transitional pieces as different surfaces can be the same height.
<b>Available in two thicknesses</b>	FlexiKork® is available in 2 thicknesses: 3 mm (1/8") is available in 100 & 300 sq. ft. rolls 6 mm (1/4") is available in 120 sq. ft. roll.
<b>Available in rolls for simple and fast installation</b>	FlexiKork® is available in 4' (48 inches) wide rolls for fast and easy installation. Rolls out quickly, stays in place and will not shift when laid. <b><i>Just roll out and go!</i></b>
<b>Suitable for use with most polyurethane adhesives</b>	FlexiKork® can be glued down using most polyurethane adhesives, including recommended UZIN MK-200. Please see FlexiKork® Installation Instructions (Part VII) for additional adhesive recommendations.

Distributed Exclusively By:




  
 1171 Landmeier Road
   
 Elk Grove Village, IL 60007 U.S.A.
   
 Tel 866.554.4252 • Fax 847.758.9696
   
 www.FlexiKork.com • Info@FlexiKork.com