

REJUVENATOR

MAGIC OIL CARE

Periodic cleaning of a MAGIC OIL 2K finished floor

PRODUCT DESCRIPTION:

A ready-to-use water-based oil/wax emulsion for rejuvenating hardwood floors finished with PALLMANN® MAGIC OIL 2K.

SUITABLE FOR:

Periodic cleaning of a MAGIC OIL 2K finished floor. MAGIC OIL CARE is not intended as an everyday floor care product but only for occasional use to maintain the floor's desired appearance.



FEATURES - BENEFITS:

- ▶ Ready-to-use – Easy, no dilution required
- ▶ Oil/wax emulsion – Maintains luster & performance of PALLMANN® MAGIC OIL 2K
- ▶ Forgiving formula – Stress-free application
- ▶ Fast-drying – Less down time

TECHNICAL DATA:

Packaging:	1 quart plastic bottle
Shelf life:	min. 24 months
Color:	Milky when wet, clear when dry
Mixing ratio:	Ready To Use No Dilution Necessary
Working climate:	Min. 60° – 85°F (15° – 25°C); min. 60°F. Store between 50-70°F (10-20°C). Keep from freezing.
Drying time:	approx. 20 minutes
VOC	< 2 g/L

At 70°F and 65% rel. humidity

PREPARATION:

1. Remove loose dirt and dust with a mop, broom or vacuum.
2. Shake PALLMANN® MAGIC OIL CARE for 30 seconds. It is recommended to ventilate the work area during application.
3. Squeeze the MAGIC OIL CARE bottle to apply an even layer of product over an area that can be mopped in a few seconds. Using a dampened PALLMANN® MICROFIBER MOP, spread material working with the grain of the wood. Continue the process until the entire floor is coated. Be careful not to leave heavy lap lines or pooling.
4. Allow the floor to dry 20 minutes before resuming foot traffic.

IMPORTANT

- ▶ Frequency of application of MAGIC OIL CARE will be dependent on the floor's location and level of use.
- ▶ PALLMANN® HARDWOOD FLOOR CLEANER can be used to clean wood floors 12 hours after application of MAGIC OIL CARE.
- ▶ Regular maintenance with PALLMANN® MAGIC OIL CARE maintains visual appearance of floor, and maintains protection of wood floors finished with MAGIC OIL 2K.
- ▶ This product is not intended as a everyday cleaner. If MAGIC OIL CARE is over-used, build up will occur.

ADDITIONAL NOTES:

Clean Up

Tools and applicators should be cleaned with water.

Storage

Minimum 24 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers.

Keep from freezing.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Read and follow all safety and environmental precautions and instructions on the packaging label and the Safety Data Sheet (SDS). The SDS is available at www.pallmann.us.

DISPOSAL:

For disposal and recycling, follow the applicable laws and regulations. When possible, avoid or minimize waste generation. Do not allow the material to get into sewers, waterways or unlined ground surfaces. Empty packaging can be recycled.

INDOOR AIR QUALITY INFORMATION

VOC content: < 2 g/L, compliant with SCAQMD 1113