Product Datasheet



ADHESIVE

PALLMANN P13

Tongue & Groove Adhesive

PRODUCT DESCRIPTION:

Quick-drying dispersion wood adhesive for gluing the tongue and groove on prefinished wood and laminate flooring. Also suitable for use as a universal wood adhesive on many wood species and wood-based materials.



FEATURES - BENEFITS:

- ▶ Excellent for gluing wood plugs and dowels
- ► For indoor use only
- ► Solvent-free

TECHNICAL DATA:

Packaging:	28.5 oz plastic bottle
Shelf life:	12 months
Color:	White
Coverage:	80 – 500 lineal feet per bottle depending on joint size
Working climate:	Above 60 °F (surface temp.)
Drying time:	5 – 10 minutes
Final strength:	After 1 – 2 days
VOC	< 40 g/L
At 68°F and 65% relative humidity	

APPLICATION:

Cut off nozzle tip to fit desired joint size. Apply P13 to the surface of the tongue or into the groove. Join wood parts together during dry time, applying force if necessary with a wooden tapping block and/or straps. Remove all traces of extruded glue immediately with a damp cloth or PALLMANN® Clean Box.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Do not handle until all safety instructions have been read and understood. Safety Data Sheet (SDS) is available at www.pallmann.us.

DISPOSAL:

Dispose of the product and packaging according to all federal, state, and local applicable regulations. Avoid or minimize waste generation when possible. Cardboard packaging is recyclable.

INDOOR AIR QUALITY INFORMATION

VOC content: < 40 g/L, compliant with SCAQMD Rule 1168