# CLEAN STRONG

# Super cleaner for Hardwood Floors and for recoat preparation.

### **PRODUCT DESCRIPTION:**

PALLMANN® CLEAN STRONG is a cleaning emulsion specially formulated to remove surface contamination from wood fl oors including dirt, grease, wax and most maintenance products in preparation for the application of PALLMANN® PALL-X BOND Recoat Adhesion System.

This product is for professional use only.

## SUITABLE FOR:

- Site finished or factory finished wood flooring, solid or engineered
- Finished cork flooring

## NOTE:

**IMPORTANT:** PALLMANN® CLEAN STRONG is a very aggressive surface cleaning product. Test a small area of the floor prior to cleaning the entire floor surface. CLEAN STRONG may damage the existing finish if left on the surface for an extended period of time. Do not use on a floor finished with MAGIC OIL 2K. Severe permanent damage to floor will occur.



#### **TECHNICAL DATA:**

Packaging:	1 quart plastic bottle
Shelf life:	Min. 24 months
Color:	Clear
Mixing ratio:	Dilution Ratio Normal Soiling: 1:10 (1 part Clean Strong to 10 parts water) Heavy Soiling: Undiluted
Working climate:	Store between 50-70°F (10-20°C). Keep from freezing.
VOC	< 210 g/L

# PREPARATION:

## Preparation

1. Remove loose dirt and dust with a mop, broom or vacuum.

PALLMANN

2. Shake PALLMANN® CLEAN STRONG for 30 seconds.

3a. **Normal Soiling** - Dilute CLEAN STRONG 1 part (Clean Strong) 10 parts (water) in clean spray bottle. Lightly mist  $4 \times 8$  area allowing product to sit 2 - 3 minutes. Begin buffing floor with a green or red pad. Work in sections small enough to keep the floor wet during the process. When Deep Cleaning a wood floor, only use a white polishing pad on a buffer. Failure to do so will cause permanent scratching in the finished wood floor.

3b. **Heavy Soiling** - Use PALLMANN® CLEAN STRONG undiluted, using a black or green pad.

4. Immediately rinse floor with a clean, lint-free towels or cloths. Do not oversaturate the floor during this procedure. Perform a second rinsing of floor to remove all residues. May use the PALLMANN TURBO SCRUBBER to remove residues and rinse floor.

5. Let the floor dry completely

**Note:** When recoating a floor previously finished with PALLMANN® MAGIC OIL 2K, PALLMANN® MAGIC OIL CLEAN N PREP is the recommended floor preparation cleaner.

PH Value: 10 (alkaline)

**Dilution Ratio:** Normal Soiling: 1:10 (1 part Clean Strong to 10 parts water).

Heavy Soiling: Undiluted

## **ADDITIONAL NOTES:**

#### Storage

Minimum 24 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers. **Keep from freezing.** 

#### CAUTION

Keep out of reach of children. Keep container closed during storage. Avoid contact with eyes and skin. Avoid breathing vapors. Use only in well-ventilated areas. Use of protective gloves (rubber) and safety glasses is recommended. Nonflammable. FIRST AID: In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with large amounts of water for at least 15 minutes and obtain medical treatment. If swallowed, obtain medical treatment immediately

1 / 2

PALLMANN | A brand of UZIN UTZ



# PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Read and follow all safety and environmental precautions and instructions on the packaging label and the Safety Data Sheet (SDS). The SDS is available at www.pallmann.us.

## DISPOSAL:

For disposal and recycling, follow the applicable laws and regulations. When possible, avoid or minimize waste generation. Do not allow the material to get into sewers, waterways or unlined ground surfaces. Empty packaging can be recycled.



The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage at us.pallmann.net | 02/2024